



ANCHOR CLEATS



ADARAC™ Anchor Cleats provide a strong, adjustable tie-down solution for your ADARAC™ Truck Bed Rack. Freely reposition along the cross bars to create anchor points exactly where needed, offering versatile options for securing all types of loads. The slim, low-profile design maximizes functionality while providing reliable holding power.

**Maximum capacity: 100 lbs. per tie down cleat. Set of 2.**

See inside for instructions.

100725 2000144\_F



**WARNING:**

Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## ANCHOR CLEAT INSTRUCTIONS

**REQUIREMENT:** ADARAC™ Cross Bars with mounting channels.

**TOOLS:** Protective eyewear, in-lb torque wrench with 9/16" socket.

**⚠ WARNING:** Each anchor cleat has a maximum load capacity of 100 lbs. DO NOT EXCEED this capacity.

### SAFETY INFORMATION

Always follow safety information in ADARAC™ Installation Instructions (available at [adarac.com](http://adarac.com)).

### CROSS BAR INSTALLATION:

A. Under cross bar, tilt (2) channel nuts into mounting channel with extended threads facing up.

B. Align anchor cleat with channel nuts then insert bolts and tighten.

D. Torque bolts to 120 in-lbs (10 ft-lbs).

E. Repeat for remaining anchor cleat.

