



MOUNTING PLATES



Easily reposition ADAGRID™ Mounting Plates along accessory bars to adjust spacing for rooftop tents, roof cargo baskets and other bolt-on overlanding platform accessories. The durable construction keeps gear securely in place during demanding off-road conditions, while the user-friendly design makes installation and removal quick and hassle-free.

Maximum capacity: 75 lbs. per mounting plate, do not exceed rack weight rating.

See inside for instructions.

100725 4007439_C



WARNING:

Cancer and Reproductive Harm
www.P65Warnings.ca.gov



MOUNTING PLATE INSTRUCTIONS

TOOLS: Protective eyewear and ft-lb torque wrench with 9/16" socket.

⚠ WARNING: Each mounting plate has a maximum load capacity of 75 lbs. DO NOT EXCEED this capacity.

SAFETY INFORMATION

- Always follow safety information in ADARAC™ and ADAGRID™ Installation Instructions (available at adarac.com).
- Only use ADAGRID™ Mounting Plates with bolt on accessories.

A. Insert (2) mounting brackets in bottom nut channel of ADAGRID™ Accessory Bar.

IMPORTANT: Ensure extended threads on mounting brackets face up.

TIP: If installing optional accessories, insert mounting hardware in bottom nut channel of accessory bar before attaching to cross bar.

B. With mounting bracket in desired location, align holes in mounting plate with holes in mounting bracket.

C. Insert bolts through mounting plate into mounting bracket, then finger tighten.

D. Torque bolts to 32 ft-lbs.

E. Repeat Steps A-D for remaining mounting plates.

