



31086 INSTALLATION INSTRUCTIONS



Safety glasses should be worn at all times while installing this product.

YEARS: 2018-PRESENT

MAKE: JEEP

MODEL: WRANGLER

STYLE: SUV



WARNING: NEVER EXCEED YOUR VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY
For more information log onto www.curtmfg.com & for helpful towing tips log onto www.hitchinfo.com

WEIGHT CARRYING:

TRAILER WEIGHT: 3,500 LBS.
TONGUE WEIGHT: 350 LBS.

GROSS LOAD CAPACITY WHEN USED AS A STRAIGHT LINE PULL:
9,000 LBS MAX.

PRO INSTALL TIME: 45 MIN.

NOVICE INSTALL TIME: 90 MIN.

IF YOU ARE HESITANT TO UNDERTAKE
THIS TASK ON YOUR OWN, CONTACT AN AUTHORIZED
CURT INSTALLER FOR ADDITIONAL ASSISTANCE.




INSTALLATION REQUIRES:

| | | |
|---|--|---|
|  RATCHET |  11/16" 8mm 16mm 17mm SOCKET |  TORQUE WRENCH |
|  TAPE MEASURE |  AVIATION SHEARS |  MASKING TAPE |
|  SAFETY GLASSES |  SCREW DRIVER | |
| | | |

INSTALLATION TIPS:

1. BEFORE YOU BEGIN INSTALLATION, READ ALL INSTRUCTIONS THOROUGHLY.
2. TO EASE INSTALLATION, 2 PEOPLE MAY BE REQUIRED.
3. USING PROPER TOOLS WILL GREATLY IMPROVE THE QUALITY OF THE INSTALL AND REDUCE THE TIME REQUIRED.
4. NEED HELP OR HAVE SOME QUESTIONS?
CALL TECHNICAL SUPPORT AT 800.798.0813

LEVEL OF DIFFICULTY: EASY


| EASY | MODERATE | CHALLENGING |
|---|---|-------------|
|  | NO DRILLING REQUIRED | |
|  | REMOVE LOWER FASCIA REMOVE AND RETURN SHIELD | |
|  | TRIM LOWER PLASTIC FASCIA PANEL | |
| | | |
| | | |

VEHICLE PHOTO:



REPRESENTATIVE PHOTO

HITCH ILLUSTRATION:



MAKE SURE YOUR HITCH MATCHES



SCAN FOR
MORE INFO

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE ALL FASTENERS ARE TIGHT AND ALL STRUCTURAL COMPONENTS ARE SOUND

CURT Manufacturing LLC. warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, CURT Manufacturing LLC. may repair or replace the product at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. CURT Manufacturing LLC.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.



For more information log onto www.curtmfg.com

This product complies with safety specifications and requirements for connecting devices and towing systems of the state of New York, V.E.S.C.Regulation V-5 and SAE J684.


3/8/2018

INSTALLATION WALKTHROUGH:



| Parts List | | | |
|------------|-----|--------------------------------------|--|
| ITEM | QTY | PART NUMBER | DESCRIPTION |
| 1 | 1 | 31086-DSFT | DRIVER SIDE FACIA TAB |
| 2 | 1 | 31086-PSFT | PASSENGER SIDE FACIA TAB |
| 3 | 4 | 7_16 - 14 x 1 1_4 CARRIAGE (GRADE 8) | CARRIAGE BOLT |
| 4 | 4 | CM-SP7 | .250 x 1.00 x 2.00" SQUARE HOLE SPACER |
| 5 | 4 | 7/16-14 | HEX FLANGE NUT |
| 6 | 2 | M10 - 1.5 x 35mm | HEX TAP BOLT |
| 7 | 2 | 7/16" | CONICAL TOOTHED WASHER |



- 1) Remove 8 plastic push fasteners from the upper edge of the lower front fascia. Using an 8mm socket, remove the (2) 5mm screws holding the lower edge of the plastic fascia. Using a 16mm socket, remove the (2) 10mm bolts holding the steel shield. Return bolts and shield to vehicle owner, but keep the (2) clip nuts for later reinstallation.



- 2) Raise hitch into position and loosely install the supplied fascia tabs, 10mm bolts and conical washers as shown above. Install the (4) 7/16" carriage bolts and spacers into the remaining mounting holes as shown above by inserting through the closest access hole.




INSTALLATION WALKTHROUGH:

- 3) Loosely install the supplied 7/16" hex flanges nuts. Torque the 10mm fasteners to 45 lb.-ft. and all 7/16" fasteners to 60 lb.-ft.

Note: The small holes in the fascia tabs should be about 31.25" apart to line up with the fascia panel mounting holes.



- 4) Trim the lower plastic fascia as shown in the Panel Trim Diagram to reinstall around the receiver tube of the hitch. Reinstall lower plastic fascia with original fasteners.



For more information log onto www.curtmfg.com

31086**JEEP WRANGLER****3/8/2018**

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 3,500 LBS. TRAILER WEIGHT & 350 LBS. TONGUE WEIGHT.
 GROSS LOAD CAPACITY WHEN USED AS A STRAIGHT LINE PULL: 9,000 LBS. MAX. LINE PULL.




WARNING: * DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY. *****



FOR MORE INFORMATION LOG ONTO WWW.CURTMFG.COM
 HAVING INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-800-798-0813

| Parts List | | | |
|------------|-----|------------------------------------|--|
| ITEM | QTY | PART NUMBER | DESCRIPTION |
| 1 | 1 | 31086-DSFT | DRIVER SIDE FACIA TAB |
| 2 | 1 | 31086-PSFT | PASSENGER SIDE FACIA TAB |
| 3 | 4 | 7_16 - 14 x 1_4 CARRIAGE (GRADE 8) | CARRIAGE BOLT |
| 4 | 4 | CM-SP7 | .250 x 1.00 x 2.00" SQUARE HOLE SPACER |
| 5 | 4 | 7/16-14 | HEX FLANGE NUT |
| 6 | 2 | M10 - 1.5 x 35mm | HEX TAP BOLT |
| 7 | 2 | 7/16" | CONICAL TOOTHED WASHER |



CENTER OF PANEL
PANEL TRIM DIAGRAM

| TOOLS REQUIRED |
|-------------------------|
| RATCHET |
| TORQUE WRENCH |
| SAFETY GLASSES |
| STRAIGHT SCREW DRIVER |
| AVIATOR SHEARS |
| 8mm, 16mm, 17mm SOCKETS |
| 11/16" SOCKET |
| TAPE MEASURE |
| MASKING TAPE |

HITCH WEIGHT: 16 LBS.


INSTALL TIME

PROFESSIONAL: 45 MINUTES

NOVICE (DIY): 90 MINUTES

INSTALL NOTES:

- REMOVE SKID SHIELD
- REMOVE LOWER FASCIA PANEL
- NO DRILLING REQUIRED
- TRIM LOWER FASCIA PANEL



INSTALLATION STEPS

- 1) Remove (8) plastic push fasteners from the upper edge of the lower front fascia. Using an 8mm socket, remove the (2) 5mm screws holding the lower edge of the plastic fascia. Using a 16mm socket, remove the (2) 10mm bolts holding the steel shield. Return bolts and shield to vehicle owner, but keep the (2) clip nuts for later reinstallation.
- 2) Raise hitch into position and loosely install the supplied fascia tabs, 10mm bolts and conical washers as shown above. Install the (4) 7/16" carriage bolts and spacers into the remaining mounting holes as shown above by inserting through the closest access hole.
- 3) Loosely install the supplied 7/16" hex flanges nuts. Torque the 10mm fasteners to 45 lb.-ft. and all 7/16" fasteners to 60 lb.-ft.

Note: The small holes in the fascia tabs should be about 31.25" apart to line up with the fascia panel mounting holes.

- 4) Trim the lower plastic fascia as shown in the Panel Trim Diagram to reinstall around the receiver tube of the hitch. Reinstall lower plastic fascia with original fasteners.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.



Scan
for more
information

CURT Manufacturing LLC., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, CURT Manufacturing LLC., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. CURT Manufacturing LLC.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.

This product complies with safety specifications and requirements for connecting devices and towing systems of the state of New York, V.E.S.C.Regulation V-5 and SAE J684.

JEEP WRANGLER

*****DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY***.**

FRONT MOUNTED ACCESSORIES

1) Do not exceed front axle Gross Weight Rating (GAWR). Consult owners manual or specification plate located on driver's door frame. Measure gross front axle weight by placing front wheels of loaded vehicle on a scale.

WARNING: Exceeding GAWR may overload the front axle and/or suspension. This could result in **accident, property damage and personal injury.**

- 2) Reposition front mounted license plate if obstructed.
- 3) Do not obstruct vehicle lights.
- 4) Allow free air flow into grille opening.
- 5) Rear wheel traction may be reduced. This could effect handling. Reduce speed and drive with caution.
- 6) Accessories extend front of vehicle. This may reduce approach angle. Use caution when parking and maneuvering.
- 7) Do not obstruct driver view.


VEHICLE RECOVERY AND WINCHING TIPS

1) Use OEM tow hooks, recovery eyes or a clevis mount for attachment of a tow strap or winch cable.

WARNING: **NEVER** use a ball and/or ball mount as an anchor point for tow strap or winch cable. Severe personal injury or death could result.

- 2) Observe winch manufacturer's recommendations, cautions and warnings.
- 3) Attach return cable to tow hook or recovery eye when using a snatch block (See figure 1).

CAUTION: Do not attach return cable to winch mount. This may overload winch mount and/or front mounted receiver.



RATING

For **Maximum** line pull rating, winch cable must not exceed:

- 15 degree angle up or down from horizontal (See Figure 2).
- 45 degree angle left or right from straight ahead (See Figure 3).

CAUTION: Exceeding the maximum line pull rating may over load winch, winch mount, and/or front mounted receiver.

